



FILL BELLOW WITH TREMPROOF 6100

ELASTOMERIC SHEETING  
EMBEDDED IN TREMPROOF 6100

TREMCO PROTECTION COURSE

FACTORY APPLIED AND CURED  
TRAFFIC-GRADE SILICONE TOPPING

FIELD APPLIED SILICONE SEALANT  
(BOTH SIDES OF JOINT)  
SILICONE SEALANT SUPPLIED

WILLSEAL CLOSED CELL FOAM  
WITH ENGINEERED PROFILE

FIELD APPLIED EPOXY  
(BOTH SIDES OF JOINT)  
EPOXY SUPPLIED

VARIES

NOTE: REFER TO TREMCO'S PUBLISHED APPLICATION INSTRUCTIONS FOR ACCEPTABLE JOINT SIDE WALL SUBSTRATE CONDITIONS PRIOR TO INSTALLATION

TREMPRIME QD OR TREMCO APPROVED PRIMER MUST BE APPLIED BEFORE THE APPLICATION OF TREMPROOF 6100

*The architecture, engineering, and design of the project using the Tremco and Willseal products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Tremco and Willseal specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Willseal or Tremco to ensure you have the most recent version.*

**Willseal Color Coreséal H**



Detail: Willseal Color Coreséal H with TREMProof 6100 at Floor to Wall Expansion Joint

File Name:

Drawn by: HDE

Checked by: AM/WH

Scale: NTS

Date: 5/16/2022

WCCH-FW-6100-01



Construction Products Group

Willseal Technical Support: 800-274-2813

[www.tremcocpg.com](http://www.tremcocpg.com)